



# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)  
Issue date: 12/1/2022 Revision date: 12/28/2022 Supersedes: 12/1/2022 Version: 1.1

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : 4930 Polyurea Crack & Spall Filler A-Component

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Consumer products

#### 1.3. Supplier

Versatile Building Products  
1900 Lakeway Dr. Suite 500  
Lewisville, Texas 75057  
T 1-800-535-3325

#### 1.4. Emergency telephone number

Emergency number : 1-800-535-3325 (Monday - Friday 7 am - 5 pm Central Time)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin corrosion/irritation Category 1

Serious eye damage/eye irritation Category 1

Skin sensitization, Category 1

Causes severe skin burns and eye damage

Causes serious eye damage

May cause an allergic skin reaction

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Causes severe skin burns and eye damage

May cause an allergic skin reaction

Causes serious eye damage

Precautionary statements (GHS US) :

Do not breathe vapors, mist, spray.

Wash hands, forearms and face thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves, eye protection.

If swallowed: rinse mouth. Do NOT induce vomiting.

If on skin: Wash with plenty of soap and water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER, a doctor.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container to a hazardous or special waste collection point.

# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%
tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	CAS-No.: 136210-30-5	40 – 50
Aspartic Ester	CAS-No.: 152637-10-0	5 – 10
Isophorone diamine isobutyraldimine	CAS-No.: 54914-37-3	5 – 10
1,1',1'',1'''-ethylenedinitrotetrapropan-2-ol	CAS-No.: 102-60-3	6 – 8.5
Hexamethylene diisocyanate, oligomerisation product (isocyanurate type)	CAS-No.: 28182-81-2	3 – 6

The specific chemical component identities and/or the exact component percentages of this material may be withheld as trade secrets.

This information is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of 29 CFR 1910.1200 (I)(1). Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, mutagen, and reproductive toxicant, respiratory tract and skin sensitizers in addition to oral/ inhalation acute toxicant in category 1 and 2). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.  
Incompatible materials : Keep away from any possible contact with water, because of violent reaction and possible flash fire.  
Maximum storage period : 12 months  
Storage temperature : 72 °F Dry

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 4930 Polyurea Crack & Spall Filler A-Component

No additional information available

#### tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate (136210-30-5)

No additional information available

# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

<b>1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol (102-60-3)</b>
No additional information available
<b>Aspartic Ester (152637-10-0)</b>
No additional information available
<b>Isophorone diamine isobutyraldimine (54914-37-3)</b>
No additional information available
<b>Hexamethylene diisocyanate, oligomerisation product (isocyanurate type) (28182-81-2)</b>
No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : gel.  
Color : light brown  
Odor : Sweet acidic  
Odor threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Flammability : Not applicable.  
Vapor pressure : No data available  
Relative vapor density at 20°C : No data available  
Relative density : No data available

# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Density	: 8.42 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Water, humidity.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

<b>1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol (102-60-3)</b>	
LD50 oral rat	2890 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
ATE US (oral)	2890 mg/kg body weight
<b>Isophorone diamine isobutyraldimine (54914-37-3)</b>	
LD50 oral rat	4150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 3517 - 4897
LD50 dermal rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ATE US (oral)	4150 mg/kg body weight

# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

<b>Hexamethylene diisocyanate, oligomerisation product (isocyanurate type) (28182-81-2)</b>	
LD50 oral rat	> 2500 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: other:

Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

<b>Hexamethylene diisocyanate, oligomerisation product (isocyanurate type) (28182-81-2)</b>	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

<b>Isophorone diamine isobutyraldimine (54914-37-3)</b>	
LOAEL (oral,rat,90 days)	160 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

<b>1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol (102-60-3)</b>	
LC50 - Fish [1]	≈ 4600 mg/l Test organisms (species): Leuciscus idus
LOEC (chronic)	> 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

<b>Isophorone diamine isobutyraldimine (54914-37-3)</b>	
LC50 - Fish [1]	> 53.7 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	14.7 mg/l Test organisms (species): Daphnia magna

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>Isophorone diamine isobutyraldimine (54914-37-3)</b>	
Partition coefficient n-octanol/water (Log Pow)	7.16 Source: Episuite

### 12.4. Mobility in soil

No additional information available

# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

### 14.1. UN number

DOT NA No : UN1760  
UN-No. (IMDG) : 1760  
UN-No. (IATA) : 1760

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s. (CONTAINS : Isophorone diamine isobutyraldimine)  
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S.  
Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 8  
Hazard labels (DOT) : 8



#### IMDG

Transport hazard class(es) (IMDG) : 8  
Hazard labels (IMDG) : 8



#### IATA

Transport hazard class(es) (IATA) : 8  
Hazard labels (IATA) : 8



### 14.4. Packing group

Packing group (DOT) : I  
Packing group (IMDG) : I  
Packing group (IATA) : I

# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT) : UN1760

DOT Special Provisions (49 CFR 172.102) : A7 - Steel packaging must be corrosion-resistant or have protection against corrosion.  
B10 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks, and DOT 57 portable tanks are not authorized.  
T14 - 6 mm Prohibited 178.275(g)(3).  
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where:  $t_r$  is the maximum mean bulk temperature during transport,  $t_f$  is the temperature in degrees celsius of the liquid during filling, and  $a$  is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling ( $t_f$ ) and the maximum mean bulk temperature during transportation ( $t_r$ ) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where:  $d_{15}$  and  $d_{50}$  are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.  
TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Non Bulk (49 CFR 173.xxx) : 201

DOT Packaging Bulk (49 CFR 173.xxx) : 243

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 0.5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 2.5 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

#### IMDG

Special provision (IMDG) : 274

Limited quantities (IMDG) : 0

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P001

Tank instructions (IMDG) : T14

Tank special provisions (IMDG) : TP2, TP27

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE

EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : B

Properties and observations (IMDG) : Causes burns to skin, eyes and mucous membranes.

#### IATA

PCA Excepted quantities (IATA) : E0

PCA Limited quantities (IATA) : Forbidden

PCA limited quantity max net quantity (IATA) : Forbidden

PCA packing instructions (IATA) : 850

PCA max net quantity (IATA) : 0.5L

CAO packing instructions (IATA) : 854

CAO max net quantity (IATA) : 2.5L

Special provision (IATA) : A3, A803

ERG code (IATA) : 8L



# 4930 Polyurea Crack & Spall Filler A-Component

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	CAS-No. 136210-30-5	40 – 50%
Propane-1,2-diol, propoxylated (Glycol Heavies)	CAS-No. 25322-69-4	7 – 7.5%
Aspartic Ester	CAS-No. 152637-10-0	5 – 10%

### methanol (67-56-1)

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Revision date : 12/28/2022

ICSDS\_SDS\_USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.