



4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)
Issue date: 12/1/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 4930 Crack & Spall Filler B-Component

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Industrial use
Consumer products

1.3. Supplier

Versatile Building Products
1900 Lakeway Dr. Suite 500
Lewisville, Texas 75057
T 1-800-535-3325

1.4. Emergency telephone number

Emergency number : 1-800-535-3325 (Monday - Friday 7 am - 5 pm Central Time)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Respiratory sensitization, Category 1	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
Skin sensitization, Category 1	May cause an allergic skin reaction
Carcinogenicity Category 2	Suspected of causing cancer (oral)
Specific target organ toxicity (single exposure) Category 2	May cause damage to organs (respiratory system) (oral)
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 2	May cause damage to organs (respiratory system) through prolonged or repeated exposure (oral)

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Causes skin irritation
May cause an allergic skin reaction
Causes serious eye irritation
May cause an allergy or asthma symptoms or breathing difficulties if inhaled
May cause respiratory irritation
Suspected of causing cancer (oral)
May cause damage to organs (respiratory system) (oral)
May cause damage to organs (respiratory system) through prolonged or repeated exposure (oral)

Precautionary statements (GHS US) :

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe vapors, mist, spray.

4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves.
[In case of inadequate ventilation] wear respiratory protection.
If on skin: Wash with plenty of soap and water.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Call a doctor, a POISON CENTER.
If exposed or concerned: Get medical advice/attention.
Call a poison center or doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
Specific treatment (see supplemental first aid instruction on this label).
If skin irritation occurs: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a doctor.
Take off contaminated clothing and wash it before reuse.
Wash contaminated clothing before reuse.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Hexamethylene diisocyanate, oligomerisation product (isocyanurate type)	CAS-No.: 28182-81-2	30 – 40
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate	CAS-No.: 101-68-8	15 – 30
Polymeric Diphenylmethane Diisocyanate (pMDI)	CAS-No.: 9016-87-9	9 – 20
Hexamethylene diisocyanate	CAS-No.: 822-06-0	0.1 – 0.5

The specific chemical component identities and/or the exact component percentages of this material may be withheld as trade secrets.

This information is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of 29 CFR 1910.1200 (l)(1). Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, mutagen, and reproductive toxicant, respiratory tract and skin sensitizers in addition to oral/ inhalation acute toxicant in category 1 and 2). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents.

4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 4: First-aid measures

4.1. Description of first aid measures

No additional information available

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

No additional information available

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

No additional information available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

No additional information available

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a dry place.
Incompatible materials	: Keep away from any possible contact with water, because of violent reaction and possible flash fire.
Maximum storage period	: 12 months

4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

4930 Crack & Spall Filler B-Component	
No additional information available	
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Methylene bisphenyl isocyanate (MDI)
ACGIH OEL TWA [ppm]	0.005 ppm
Remark (ACGIH)	TLV® Basis: Resp sens
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Methylene bisphenyl isocyanate (MDI)
OSHA PEL C	0.2 mg/m ³
OSHA PEL C [ppm]	0.02 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Polymeric Diphenylmethane Diisocyanate (pMDI) (9016-87-9)	
No additional information available	
Hexamethylene diisocyanate, oligomerisation product (isocyanurate type) (28182-81-2)	
No additional information available	
Hexamethylene diisocyanate (822-06-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Hexamethylene diisocyanate
ACGIH OEL TWA [ppm]	0.005 ppm (IFV - Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: URT irr; resp sens. Notations: BEI
Regulatory reference	ACGIH 2022
USA - ACGIH - Biological Exposure Indices	
Local name	1,6-HEXAMETHYLENE DIISOCYANATE
BEI	15 µg/g Kreatinin Parameter: 1,6-Hexamethylene diamine (with hydrolysis) - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2022

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: gel.
Color	: light brown
Odor	: acidic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 8.35 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Water, humidity.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)	
LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	> 9400 mg/kg Source: ECHA
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Polymeric Diphenylmethane Diisocyanate (pMDI) (9016-87-9)	
LD50 oral rat	49000 mg/kg Source: Corporate Solution From Thomson Micromedex
LD50 dermal rabbit	> 9500 mg/kg Source: Corporate Solution From Thomson Micromedex
ATE US (oral)	49000 mg/kg body weight
ATE US (vapors)	0.49 mg/l/4h

Hexamethylene diisocyanate, oligomerisation product (isocyanurate type) (28182-81-2)	
LD50 oral rat	> 2500 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: other:

Hexamethylene diisocyanate (822-06-0)	
LD50 dermal rat	> 7000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	0.124 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:, 95% CL: 111 - 140
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer (oral).

4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)	
IARC group	3 - Not classifiable

Polymeric Diphenylmethane Diisocyanate (pMDI) (9016-87-9)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : May cause damage to organs (respiratory system) (oral). May cause respiratory irritation.

4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)	
STOT-single exposure	May cause respiratory irritation.

4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Polymeric Diphenylmethane Diisocyanate (pMDI) (9016-87-9)	
STOT-single exposure	May cause damage to organs. May cause respiratory irritation.
Hexamethylene diisocyanate, oligomerisation product (isocyanurate type) (28182-81-2)	
STOT-single exposure	May cause respiratory irritation.
Hexamethylene diisocyanate (822-06-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (respiratory system) through prolonged or repeated exposure (oral).
4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

SECTION 12: Ecological information

12.1. Toxicity

4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)	
LC50 - Fish [1]	> 3000 mg/l Source: ECHA
NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)	
Partition coefficient n-octanol/water (Log Pow)	4.51 Source: ECHA
Polymeric Diphenylmethane Diisocyanate (pMDI) (9016-87-9)	
Partition coefficient n-octanol/water (Log Pow)	10.46 Source: Quantitative Structure Activity Relation

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

No additional information available

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

14.1. UN number

Not regulated for transport

4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

4,4'-methylenediphenyl diisocyanate, diphenylmethane-4,4'-diisocyanate (101-68-8)

Subject to reporting requirements of United States SARA Section 313
Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
-----------	---------

Polymeric Diphenylmethane Diisocyanate (pMDI) (9016-87-9)

Subject to reporting requirements of United States SARA Section 313

4930 Crack & Spall Filler B-Component

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Hexamethylene diisocyanate (822-06-0)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb

methanol (67-56-1)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

ICSDS_SDS_USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.