

# VERSATILE

## 5085 POLYASPARTIC

### ULTRA-HIGH SOLIDS FLOOR COATING

5085 Polyaspartic Ultra- High Solids Polyaspartic Floor Coating is designed for easier application with fast dry times. The 5085 Polyaspartic was developed for Floor Coating Installers/ Contractors that might be a little hesitant about the working time of Polyaspartics due to its reputation of having rapid cure times. As part of the development process, the 5085 was tested in real-world conditions by experienced installers across the United States.

These long-time customers of Versatile reported real world working times of 35-50 minutes in temperatures ranging up to 88 degrees with 61 percent humidity. This testing has shown that the 5085 Polyaspartic Ultra-High Solids Polyaspartic Floor Coating provides superior pot life and working time when compared to traditional polyaspartic concrete floor coatings without giving up much of the early cure time that polyaspartics are known for.

### FEATURES & ADVANTAGES

- High build - 85% Solids
- Under 50 g/l VOC
- Low odor
- High Gloss
- Good resistance to most chemicals
- Non-Yellowing
- Will cure at temperatures just above freezing
- Long Pot Life & Working Time
- Foot Traffic in as little as 3-4 Hours
- Available in SD Slow Dry version



[WWW.VERSATILE.NET](http://WWW.VERSATILE.NET)

214.807.6878